

SEISMIC RESPONSE CONTROL OF IRREGULAR STRUCTURES USING NONLINEAR DAMPERS

Rakesh K. GOEL¹

SUMMARY

This paper compares the seismic response of one-story, one-way asymmetric systems with supplemental linear and non-linear fluid viscous damping. It is shown that damper non-linearity leads to minor to moderate reduction in system responses except for non-linear systems with very short periods; for such systems the edge deformations and base torque can be significantly reduced. Furthermore, the reduction in the damper forces due to damper non-linearity is not significant.

INTRODUCTION

Observations of performance of structures during past earthquakes around the world demonstrate that buildings with unsymmetrical (or irregular) floor plan suffer greater damage [1-6]. For example, statistics of building damage in Mexico City during the 1985 Michoacan earthquake show that 15% of the buildings that suffered severe damage or collapse had pronounced asymmetry, and 40% were buildings located at street corners, with less structural resistance on the street sides [1, 2]. There is a large stock of such highly vulnerable buildings in seismically active regions of the world. Clearly, there is a need to develop cost effective methods for seismic protection of unsymmetrical plan buildings.

Although seismic codes and guidelines acknowledge the seismic vulnerability of unsymmetrical plan buildings, and attempt to provide additional strength to certain lateral load resisting elements, they fails to effectively control excessive deformations that lead to damage in the building [7]. The most appealing approach of redistributing the stiffness and/or mass properties to minimize asymmetry in the building plan is not always feasible because of architectural and/or functional constraints, or because of the significant "down time" and/or inconvenience to the occupants.

The technology of fluid viscous damping devices is appealing for seismic protection of buildings [8]. Developed initially for defense application to arrest recoil in big guns, the fluid viscous damping devices

¹ Professor, Department of Civil & Environmental Engineering, California Polytechnic State University, San Luis Obispo, CA 93407, USA.

have been shown to be effective in controlling damaging deformations in buildings during earthquake shaking, e.g., [9-11]. However, most previous work in this area has been for protection of symmetric (or regular) structures.

Seismic control of asymmetrical plan (or irregular) structures has received considerable attention in the past decade [12-23]. Several investigations have demonstrated effectiveness of supplemental fluid viscous damping in reducing seismic response of asymmetric-plan systems [13, 16, 18, 21, 24]. However, most of these investigations focused on behavior of asymmetric-plan systems with linear fluid viscous dampers. Non-linear fluid viscous dampers (velocity exponent less than one) have the apparent advantage of leveling-off of the damper force at large velocity across the damper as opposed to linear dampers (velocity exponent equal to one) for which the damper force increases linearly with damper velocity [25, 26]. Two recent investigations also examined seismic response of asymmetric systems with lateral load resisting systems responding in the linear elastic range of behavior. It would also be useful to investigate these effects on systems in which lateral load resisting elements are deformed beyond the elastic limit.

Therefore, the main objectives of this research investigation are to (1) evaluate the effects of damper nonlinearity on seismic response of nonlinear asymmetric systems; and (2) evaluate how the effects of plan-asymmetry are influenced by the damper nonlinearity. For reference purposes, responses of linear systems are also included.

In order to understand the behavior of nonlinear fluid viscous dampers, summarized first is the theoretical background on nonlinear fluid viscous dampers. The effects of damper nonlinearity are investigated next by comparing normalized values of seismic responses – edge deformations, base shear and torque, and total damping force and torque at the base – of one-story, one-way asymmetric linear and nonlinear systems having nonlinear fluid viscous dampers (velocity exponent $\alpha = 0.7, 0.5, \text{ and } 0.35$) with those for systems having linear fluid viscous damper (velocity exponent $\alpha = 1$). The effects of plan-asymmetry are investigated by normalizing the response of asymmetric-plan systems with supplemental dampers with the response of the corresponding symmetric-plan system – a system with relative location and stiffness of all resisting elements as well as location, damping coefficient, and damping exponent of all supplemental dampers identical to those in the asymmetric-plan system but with the rotational degree-of-freedom restricted. These normalized responses in systems with nonlinear dampers are compared with those in systems with linear dampers to examine how the damper nonlinearity modifies the effects of plan-asymmetry.

THEORETICAL BACKGROUND

Force in Nonlinear Fluid Viscous Damper

The force in a nonlinear fluid viscous damper is given by

$$f_D = C_\alpha \operatorname{sgn}(\dot{u}) \left| \dot{u} \right|^\alpha \tag{1}$$

in which C_{α} is the damper coefficient, \dot{u} is the damper velocity, $sgn(\cdot)$ is the signum function, and α is the damper exponent ranging in values from 0.2 to 1 for seismic applications [26, 29-31]. For $\alpha = 1$, equation (1) becomes $f_D = C_1 \dot{u}$ which represents force in a linear damper. Therefore, exponent α is representative of the nonlinearity of a fluid viscous damper.

For a single-degree-of-freedom (SDF) system with mass *m*, stiffness *k*, and a nonlinear fluid viscous damper defined by equation (1), the supplemental damping ratio ζ_{sd} is defined based on the concept of equivalent linear viscous damping [26, 30-32] as follows:

$$\zeta_{sd} = \frac{E_D}{4\pi E_{so}} = \frac{E_D}{2\pi k u_o^2} \tag{2}$$

where E_{so} is the elastic energy stored at the maximum system displacement, u_0 . The energy dissipated by the damper E_D is usually computed as that during one cycle of harmonic motion $u = u_0 \sin \omega t$ at $\omega = \omega_n$ (ω_n = natural frequency of the SDF system) and is given by [26, 29-31]:

$$E_D = \pi \beta_\alpha C_\alpha \omega_n^\alpha u_o^{1+\alpha} \tag{3}$$

where the constant β_{α} is

$$\beta_{\alpha} = \frac{2^{2+\alpha} \Gamma^2 \left(1 + \alpha/2\right)}{\pi \Gamma(2+\alpha)} \tag{4}$$

and $\Gamma(\cdot)$ is the gamma function. Equation (1) can also be written in an alternative but equivalent form [33]. Utilizing equation (3) in equation (2) gives ζ_{sd} as a function of the peak displacement u_0 :

$$\zeta_{sd} = \frac{\beta_{\alpha} C_{\alpha}}{2m\omega_n} (\omega_n u_o)^{\alpha - 1}$$
(5)

Therefore, for a given value of supplemental damping ratio, ζ_{sd} , the damper coefficient of a nonlinear damper with damper exponent of α can be calculated as

$$C_{\alpha} = \frac{2m\omega_n \zeta_{sd}}{\beta_a} (\omega_n u_o)^{1-\alpha}$$
(6)

For a linear damper with $\alpha = 1$, equation (6) gives $C_1 = 2m\omega_n \zeta_{sd}$ implying that the damping coefficients of a nonlinear and linear damper, both with same damping ratio, ζ_{sd} , are related as:

$$C_{\alpha} = \frac{\left(\omega_n u_o\right)^{1-\alpha}}{\beta_{\alpha}} C_1 \tag{7}$$

Utilizing equation (7), equation (1) can be re-written as:

$$\frac{f_D(t)}{f_{Do}(\alpha=1)} = \frac{1}{\beta_{\alpha}} \left(\frac{\omega_n u_o}{\dot{u}_o}\right)^{1-\alpha} \operatorname{sgn}(\dot{u}) |\dot{u}|^{\alpha}$$
(8)

and the peak value of the damper force is given as:

$$\frac{f_{Do}(\alpha)}{f_{Do}(\alpha=1)} = \frac{1}{\beta_{\alpha}} \left(\frac{V}{\dot{u}_{o}}\right)^{1-\alpha}$$
(9)

in which $V = \omega_n u_0$ is the pseudo-velocity for the SDF system.

It is usual to define C_{α} when the system is subjected to harmonic motion with peak displacement equal to the design displacement u_{des} . For this case, the damper force is given by:

$$\frac{f_{Do}(\alpha)}{C_1 \omega_n u_{des}} = \frac{1}{\beta_{\alpha}} \left(\frac{\dot{u}_o}{\dot{u}_{des}} \right)^{\alpha}$$
(10)

It is useful to emphasize that equation (10) represents the relationship between force and velocity of a nonlinear damper for which the damping coefficient C_{α} is defined at u_{des} . Therefore, the damping ratio is equal to ζ_{sd} only at displacement equal to u_{des} ; for displacements (and hence velocities) either lower or higher than u_{des} , the equivalent damping ratio would not be equal to ζ_{sd} . For systems in which the damping ratio is equal to ζ_{sd} at all displacements, the damper force is given by:

$$\frac{f_{Do}(\alpha)}{C_1 \omega_n u_{des}} = \frac{1}{\beta_{\alpha}} \left(\frac{\dot{u}_o}{\dot{u}_{des}} \right)$$
(11)

Behavior of Nonlinear Fluid Viscous Dampers

Figure (1a) presents the force-displacement response (or hysteresis loops) of linear ($\alpha = 1$) and nonlinear ($\alpha = 0.35$ and 0) fluid viscous dampers with equivalent damping ratio ζ_{sd} when subjected to harmonic motion. The hysteresis loop for the linear damper ($\alpha = 1$) is well known- elliptical shape whereas that of nonlinear damper with $\alpha = 0$ (friction damper) is rectangular; the shape for nonlinear damper with $0 < \alpha < 1$ fall between these two extremes. Because all hysteresis loops enclose same area (ζ_{sd} was defined based on equal energy dissipation or equal area), the peak damper force in nonlinear damper ($\alpha < 1$) is less than that for the linear damper ($\alpha = 1$). For systems subjected to harmonic motion, equation (9) simplifies to $f_{D_0}(\alpha)/f_{D_0}(\alpha)=1/\beta_{\alpha}$, which gives 0.785 ($=\pi/4$) for $\alpha = 0$ and 0.866 for $\alpha = 0.35$. This indicates that the peak damper force in friction damper is about 22% and 13% less in nonlinear dampers with $\alpha = 0$ and 0.35, respectively, compared to the linear damper.

The reductions in peak damper force noted in Figure (1a) occur for system subjected to harmonic motion; similar level of reduction may not occur when the same system is subjected to ground motions. To investigate this, plotted in Figure (1b) is the relationship between the damper force and ratio of the psuedo-velocity and peak velocity, V/\dot{u}_o (equation 9). Note that for systems subjected to harmonic motions, $V/\dot{u}_o = 1$, and the peak force in nonlinear damper is less than that in the linear damper (Figure 1b). For values of V/\dot{u}_o larger than a certain threshold value, the force in nonlinear damper may become larger than that in the linear damper. The threshold value occurs for $V/\dot{u}_o = \beta_{\alpha}^{1/(1-\alpha)}$ (= 1.27, 1.25, and 1.23, for $\alpha = 0, 0.7$, and 0.35, respectively). For earthquake ground motions, the ratio V/\dot{u}_o can be larger than one for very-short period systems [32: Sec 6.12], and as a result the force in nonlinear damper may be larger than in linear damper.

Figure (1c) presents the relationship of equation (10) for nonlinear damper with its damping coefficient defined to give equivalent ζ_{sd} at peak displacement of u_{des} . At value of \dot{u}_o/\dot{u}_{des} larger than certain threshold value, the peak force in nonlinear damper is less than that in the linear damper; the threshold value of \dot{u}_o/\dot{u}_{des} is less than one and depends on α . Furthermore, the peak force tends to reach a upper bound in nonlinear damper with increasing values of \dot{u}_o/\dot{u}_{des} , as apparent from flattening of the curves for $\alpha < 1$; the force in linear damper keeps on increasing linearly with \dot{u}_o/\dot{u}_{des} . This indicates that damper

nonlinearity tends to limit the damper force at velocities in excess of the design velocity. This behavior is generally cited as a major advantage of nonlinear dampers over the linear dampers. However, it must be noted that for values of $\dot{u}_o/\dot{u}_{des} > 1$, the equivalent damping provided by the nonlinear damper is smaller compared to its design value (Fig. 1d). For $\dot{u}_o/\dot{u}_{des} < 1$, on the other hand, nonlinear damper provide larger damping ratio compared to the design value.

The behavior of nonlinear dampers that provide damping ratio equal to selected ζ_{sd} value at all displacements and velocities (equation 11) is plotted in Figure (1e). It is apparent from these results that the peak force increases linearly for linear as well as nonlinear dampers. However, the rate of increase is lower for nonlinear dampers compared to the linear dampers. As expected, the damping ratio remains the same for all values of \dot{u}_o/\dot{u}_{des} (Figure 1f).



Figure 1. Behavior of linear and nonlinear fluid viscous dampers. SYSTEM, GROUND MOTIONS, AND RESPONSE STATISTICS

System

The system considered was the idealized one-story building of Figure 2 consisting of a rigid deck supported by structural elements (wall, columns, moment-frames, braced-frames, etc.), and fluid viscous dampers incorporated into the bracing system. The mass properties of the system were assumed to be symmetric about both the *X*- and *Y*-axes whereas the stiffness and the damper properties were considered to be symmetric only about the *X*-axis.

The center of mass (CM) of the system coincides with the geometric center of the deck. The lack of symmetry in the stiffness properties about the *Y*-axis was characterized by the stiffness eccentricities, e, defined as the distance between the CM and the center of rigidity (CR). With both CM and CR defined, the edge that is on the same side of the CM as the CR was denoted as the stiff edge and the other edge was designated as the flexible edge (Figure 2a). The lack of symmetry in the damper properties about the *Y*-axis was characterized by the supplemental damping eccentricity, e_{sd} , defined as the distance between the CM and the center of supplemental damping (CSD) (Figure 2b). The corresponding symmetric-plan system was defined as a system with coincidental CM, CR, and CSD, but with relative locations and stiffnesses of all resisting elements as well as locations and damping coefficients of all supplemental dampers identical to those in the asymmetric-plan system. Further details of the system are available elsewhere [20, 34].



Figure 2. One-story, one-way asymmetric system considered: (a) locations of lateral force resisting elements; and (b) locations of fluid viscous dampers.

Ground Motions

The sets of 20 ground motion records were assembled for Los Angeles, Seattle, and Boston representing probabilities of exceedance of 2%, 10%, and 50% in 50 years (return periods of 2475, 475, and 72 years, respectively) [35]. The 10% probability of exceedance in 50 years set of records developed for the Los Angeles are used in this investigation.

Response Statistics

The dynamic response of each system to each of 20 ground motions is determined by response history analysis [32]. Presented in this paper are median values \hat{x} , defined as the geometric mean, of n(=20)

observed values of x_i of the peak value of the structural response [36]: $\hat{x} = \exp\left[\sum_{i=1}^{n} \ln x_i / n\right]$.

SYSTEM PARAMETERS AND RESPONSE CONSIDERED

System Parameters

The linear elastic response of one-story, asymmetric-plan systems without supplemental damping depends on (1) transverse vibration period, $T_y = 2\pi/\omega_y$ (ω_y = vibration frequency), of the corresponding symmetric-plan system in the Y-direction; (2) normalized stiffness eccentricity, $\overline{e} = e/a$ (a = plan dimension perpendicular to the direction of ground motion); (3) ratio of the torsional and transverse frequencies, Ω_{θ} ; (4) aspect ratio of the deck, $\alpha = a/d$; and (5) mass and stiffness proportional damping constants, a_0 and a_1 , which in turn depend on the natural damping ratios in the two vibration modes of the system. Detailed description of various parameters of a linear system is available elsewhere [13].

The additional parameters needed to include supplemental damping are: (1) supplemental damping ratio, ζ_{sd} ; (2) normalized supplemental damping eccentricity, $\overline{e}_{sd} = e_{sd}/a$; and (3) damper velocity exponent, α . The supplemental damping ratio for systems with nonlinear dampers is defined by equation (5), in which u_o is taken as the deformation from the median elastic response spectrum for damping ratio equal to natural damping plus the supplemental damping. This approach differs from an earlier investigation [21] that used an iterative procedure to define the damping ratio for systems with nonlinear dampers. There are two reasons for adopting this approach. First, the convergence in the iterative procedure may be difficult to obtain for systems with lateral load resisting elements responding in the nonlinear range. This is especially true for short period systems. Second, the iterative approach [21] leads to different damper coefficients to achieve a selected damping ratio for different ground motions of an ensemble. For investigations using an ensemble of ground motions, such as the present study, it may be useful to keep the damper coefficients same for all ground motions. The parameters for the linear and non-linear systems with non-linear fluid viscous dampers are further described elsewhere [20, 34].

For nonlinear systems, the strengths of lateral load resisting elements is defined as $f_{xi} = k_{xi}U_x$ and $f_{yi} = k_{yi}U_y$ in which $U_x = u_{ex}/R_x$ and $U_y = u_{ey}/R_y$ are the system yield displacements in the x- and y-directions, respectively, and R_x and R_y are the x- and y-direction strength reduction factors. It is useful to note here that strength distribution selected in this manner is consistent with the constant-D type distribution [37] and that advocated recently for asymmetric-plan systems [38]. While other strength distributions are possible, this distribution was selected for simplicity. The quantities u_{ex} and u_{ey} are taken as the x- and y-direction peak deformations of corresponding symmetric-plan system with linear viscous damping equal to natural damping plus the supplemental damping;

Responses are presented for the following values of system parameters: T_y in the range of 0.05 to 3 sec; $\Omega_{\theta} = 1$; $\overline{e} = 0.2$; aspect ratio = 2; and $\zeta = 5\%$ in all modes of the corresponding linear elastic symmetricplan system. The parameters for the supplemental damping system were selected as: $\zeta_{sd} = 20\%$; $\overline{e}_{sd} = -0.2$; and $\alpha = 1, 0.7, 0.5$, and 0.35. For nonlinear systems, R_x and $R_y = 4$ were selected; the system is expected to be excited well into the inelastic range for this value of R_x and R_y .

Response Considered

The following six response quantities are considered in this investigation: stiff- and flexible-edge deformations; base shear and base torque; and total damping force and damping torque at the base of the system. While edge deformations have been examined traditionally for asymmetric-plan systems [13], the various force quantities are included for the following reason. Behavior of linear and nonlinear fluid viscous dampers in the single-degree-of-freedom system subjected to harmonic motions indicates that the damper nonlinearity tends to limit the damper force for velocities in excess of the design velocity. While this assertion has been examined previously for symmetric systems subjected to ground motions, e.g., [33], it would be useful to examine it for asymmetric-plan systems where not only lateral forces but also torsional moments occur.

In order to evaluate the effects of damper nonlinearity, response of the asymmetric-plan system with linear and nonlinear dampers is normalized by that of the corresponding symmetric system with linear damper. These values are defined as: $U'_s = u_{s,\alpha,ASYM}/u_{o,\alpha=1,SYM}$ for the stiff-edge deformation, $U'_f = u_{f,\alpha,ASYM}/u_{o,\alpha=1,SYM}$ for the flexible-edge deformation, $V'_b = V_{b,\alpha,ASYM}/V_{b,\alpha=1,SYM}$ for the base shear, $T'_b = T_{b,\alpha,ASYM}/eV_{b,\alpha=1,SYM}$ for the base torque, $V'_d = V_{d,\alpha,ASYM}/V_{d,\alpha=1,SYM}$ for the damping force at the base, and $T'_d = T_{d,\alpha,ASYM}/eV_{d,\alpha=1,SYM}$ for the damping torque at the base. Also examined is the ratio of the response of asymmetric system with nonlinear and linear damper.

In order to investigate the effects of plan asymmetry in system with nonlinear damper, response of the asymmetric-plan system with nonlinear dampers is normalized by that of the corresponding symmetric-plan system with same nonlinear dampers. These values are defined as: $U_s^* = u_{s,\alpha,ASYM}/u_{o,\alpha,SYM}$ for the stiff-edge deformation, $U_f^* = u_{f,\alpha,ASYM}/u_{o,SYM}$ for the flexible-edge deformation, $V_b^* = V_{b,\alpha,ASYM}/V_{b,\alpha,SYM}$ for the base shear, $T_b^* = T_{b,\alpha,ASYM}/eV_{b,\alpha,SYM}$ for the base torque, $V_d^* = V_{d,\alpha,ASYM}/V_{d,\alpha,SYM}$ for the damping force at the base, and $T_d^* = T_{d,\alpha,ASYM}/eV_{d,\alpha,SYM}$ for the damping torque at the base.

EFFECTS OF DAMPER NONLINEARITY

Figures 3 presents the median values of normalized responses $-U'_s$, U'_f , V'_b , T'_b , V'_d , and T'_d – of the linear asymmetric systems with linear and nonlinear dampers whereas Figure 4 shows the ratio of the median values of the response of linear asymmetric-plan systems with nonlinear dampers and linear dampers. These results lead to the following observations.

The damper nonlinearity leads to reduction in the stiffness- and flexible-edge deformations (Figures 3a and 3b). The reduction tends to increase with decreasing values of α . The reduction for the stiff-edge is minimal: the reduction is, in general, less than 10% (Figure 4a) for the lowest value of $\alpha = 0.35$ considered in this investigation. The damper nonlinearity leads to larger reduction in the flexible-edge deformation (Figure 4b) compared to that in the stiff-edge deformation (Figure 4a). The reduction tends to be larger for short period systems and decreases as the system period increases (Figure 4b). The reduction may be as large as 30% for short period systems ($T_y < 0.5$ sec). For longer period systems, the reduction may only be by less than 10%.

The damper nonlinearity has little influence on the base shear as apparent from curves for all values of α being nearly identical (Figure 3c). The ratio of base shear in systems with nonlinear and linear damper presented in Figure (4c) confirms this observation as the ratio is nearly equal to one over the entire period range. The base torque (Figure 3d) is reduced to a much larger degree compared to the base shear (Figure 3c). The largest reduction in the base torque is about 20% for $\alpha = 0.35$ and occurs for $T_y < 0.5$ sec (Figure 4d). For longer period systems ($T_y > 2$ sec) the reduction in base torque is minimal.

As observed previously for linear and nonlinear dampers subjected to harmonic motions, the total damper force in general reduces with reducing value of α (Figure 3e) in linear asymmetric systems subjected to ground motions. The percent reduction is about 15% for $\alpha = 0.35$ over the wide range of period values considered (Figure 4e). The total damping torque at the base, however, may be increased slightly (Figure 3f); the increase may be as larger as 10% for $\alpha = 0.35$ (Figure 4f).

For systems with very short period (e.g., $T_y \le 0.1$ sec for selected parameters), the total damping force – lateral force and torque – may increase, instead of reducing, due to damper nonlinearity (Figures 3e and 3f). This increase may be as large as 25% (Figures 4e and 4f). Therefore, damping nonlinearity does not always reduce the damper force in asymmetric systems, as has been generally believed to occur for symmetric systems [25, 26, 29, 30, 39], and found in a recent investigation on asymmetric systems [27].



Figure 3. Seismic response of linear asymmetric systems with linear and nonlinear fluid viscous dampers.

Figure 4. Ratio of seismic response of linear asymmetric systems with nonlinear ($\alpha = 0.7, 0.5$, and 0.35) and linear ($\alpha = 1$) fluid viscous dampers.

In order to investigate how the effects of damper nonlinearity are modified by the system nonlinearity, the median values of normalized responses and the ratios are presented in Figures 5 and 6, respectively for nonlinear systems. These results lead to the following observations.

The trends for edge deformations in nonlinear systems (Figures 5a, 5b, 6a, and 6b) are in general similar to those for the linear systems observed earlier. The base shear may reduce slightly for long period systems (Figures 5c) with the reduction being less than 10% (Figure 6c). The base torque, however, may increase significantly (Figure 5d) with the increase being larger than 20% over a wide range of periods for $\alpha = 0.35$ (Figure 6d). The trends for total damper force and damper torque (Figures 5e, 5f, 6e, and 6f) are, however, generally similar to those observed earlier for elastic systems (Figures 3e, 3f, 4e, and 4f).

In summary, the damper nonlinearity leads to only minor (less than 10%) reduction in stiff edge deformation. The reduction in the flexible edge deformation of the order of 30% may be achieved for short period systems ($T_y < 0.5$ sec). For longer period systems, however, the reduction may only be by less than 10%. The base shear is essentially unaffected by the damper nonlinearity. The base torque may be reduced by up to 20% for short period linear and nonlinear systems but may be increased by up to 20% for longer

period nonlinear systems. The damper nonlinearity leads to about 15% reduction in the total damping force for longer period systems. For very short period systems ($T_y \leq 0.1$ sec), however, the total damping force may increase by up to 25% due to damper nonlinearity. The total damping torque at the base increases slightly over the period range considered in this investigation.







Figure 6. Ratio of seismic response of nonlinear asymmetric systems with nonlinear ($\alpha = 0.7, 0.5$, and 0.35) and linear ($\alpha = 1$) fluid viscous dampers.

EFFECTS OF PLAN-ASYMMETRY

Effects of plan-asymmetry are evaluated by examining the ratio of the response of the asymmetric-plan system and its corresponding symmetric-plan system; note that the corresponding symmetric-plan system will have the same damping ratio, ζ_{sd} , and velocity exponent, α , as the asymmetric-plan system. The median values of the ratio for six response quantities $-U_s^*$, U_f^* , V_b^* , T_b^* , V_d^* , and T_d^* – are presented in Figures 7 and 8 for linear and nonlinear systems, respectively. These results lead to the following conclusions.

The plan-asymmetry generally has the effect of increasing deformation of the flexible edge, as apparent from the ratio being generally larger than one for this edge (Figures 7b and 8b). This observation is consistent with those of several previous investigations [40, 41]. The damper nonlinearity reduces this effects; increase in the flexible-edge deformation (Figures 7b and 8b) is smaller for lower values of α . For example, median value of U_f^* for a linear system with T_y =0.5 sec may be reduced by about 18% due to damper nonlinearity (Figure 7b); U_f^* =1.388 for linear damper ($\alpha = 1$) which reduces to U_f^* =1.133 for nonlinear damper with $\alpha = 0.35$. The effects on the stiff-side elements are modified to a much smaller degree (Figures 7a and 8a) compared to the flexible-edge deformation.

The plan-asymmetry reduces the base shear of linear systems. The damper nonlinearity does not modify this trend as apparent from essentially identical curves for various values of α (Figures 7c). Since, the base shear in a nonlinear system is limited by its lateral strength, the plan-asymmetry appears to have no effect on the base shear in nonlinear systems; note that the ratio is essentially one over the entire period range (Figure 8c). As noted for linear systems, the damper nonlinearity does not further modify this trend for nonlinear systems (Figure 8c). The plan-asymmetry leads to base torque in asymmetric-plan systems, which is reduced slightly for linear systems and increased for nonlinear systems by the damper nonlinearity (Figures 7d and 8d).

The plan-asymmetry generally tends to reduce the total damping force at the base in linear systems apparent from the ratio being smaller than one for most period values (Figure 7e). The damper nonlinearity has the effect of reducing this effect, i.e., the reduction in total damping force at the base is smaller as α reduces. For nonlinear systems, the ratio is essentially one for all values of α over the entire period range (Figure 8e) indicating that effects of plan-asymmetry for such systems are minimal and they are not influenced by the damper nonlinearity. The plan-asymmetry as well as asymmetry in the damper distribution gives rise to the total damping torque at the base, which tends to increase with decreasing values of α .



Figure 7. Effects of plan-asymmetry in seismic response of linear systems with linear and nonlinear fluid viscous dampers.



In summary, the effects of plan-asymmetry on the flexible edge deformation are reduced by the damper nonlinearity. The effects on the stiff-edge deformation, base shear, and total damping force are modified very little by the damper nonlinearity. The modification for the base torque and total damping torque is slightly larger.

CONCLUSIONS

The investigation on seismic response of one-story, one-way asymmetric linear and nonlinear systems with linear and nonlinear fluid viscous dampers has led to the following conclusions:

- 1. The damper nonlinearity leads to only minor (less than 10%) reduction in stiff-edge deformation over the entire period range. The reduction of the order of 30% may be achieved in flexible-edge deformation for short period ($T_y < 0.5$ sec) systems; for longer period systems, the reduction in the flexible-edge deformation is comparable to that for the stiff-edge deformation.
- 2. The damper nonlinearity leads to minor reduction (less than 10%) in the base shear. The base torque may reduce by 20% for short period ($T_y < 0.5 \text{ sec}$) linear and nonlinear systems, but may increase by 20% for longer period ($T_y > 0.5 \text{ sec}$) nonlinear systems.
- 3. The damper nonlinearity leads to about 15% reduction in the total damping force for most periods. For very-short period (T_y ≤ 0.1 sec) systems, however, the total damping force may increase, instead of reducing, with increase being as large as 25%. The damping nonlinearity may also lead to slight increase in the total damping torque at the base over the entire period range.
- 4. The effects of plan-asymmetry on the flexible edge deformation are significantly reduced by the damper nonlinearity, especially for short period systems. The effects on the stiff-edge deformation, base shear, and total damping force are modified very little by the damper nonlinearity. The modification for the base torque and total damping torque is slightly larger.

ACKNOWLEDGEMENT

This research investigation is funded by the National Science Foundation under Grant CMS-9812414. This financial support is gratefully acknowledged.

REFERENCES

- 1. Rosenblueth E, Meli R. The 1985 earthquake: causes and effects in Mexico City. *Concrete International, ACI*, 1986: 23-24.
- 2. Esteva L. Earthquake engineering research and practice in Mexico after the 1985 earthquake. *Bulletin of New Zealand Society of Earthquake Engineering*, 1987; **20**(3): 159-200.
- 3. Benuska L, ed. Loma Prieta earthquake reconnaissance report. Supplement to Vol. 6. 1990, *Earthquake Spectra*, 448.
- 4. Holmes WT, ed. Northridge earthquake of January 17, 1994. 1995, *Earthquake Spectra*.
- 5. Comartin CD, Greene M, Tubbesing S, eds. The Hyogo-Ken Nambu earthquake of January 19, 1995: Preliminary reconnaissance Report. 1995, *Earthquake Engineering Research Institute*: Oakland, CA.
- 6. Goel RK. *Preliminary report on December 22, 2003 San Simeon earthquake*. California Polytechnic State University, 2003, http://ceenve.calpoly.edu/goel/san_simeon_eqk/index.html.
- 7. Goel RK. Seismic response of asymmetric systems: energy-based approach. *Journal of Structural Engineering*, 1997; **123**(11): 1444-1453.
- 8. Taylor DP. *History, design, and application of fluid dampers in structural engineering*. Taylor Devices, Inc., 2003, http://www.taylordevices.com/papers/history/design.htm.

- 9. Gluck N, Reinhorn AM, Gluck J, Levy R. Design of supplemental dampers for control of structures. *Journal of Structural Engineering*, 1996; **122**(12): 1394-1399.
- Constantinou MC, Symans MD. Experimental and Analytical Investigation of Seismic Response of Structures with Supplemental Fluid Viscous Dampers. *Report No. NCEER-92-0032*, National Center for Earthquake Engineering Research, Buffalo, NY, 1992.
- 11. Aiken ID, Kelly JM. Earthquake simulator testing and analytical studies of two energy-absorbing systems for multistory structures. *Report No. UBC/EERC-90/03*, Earthquake Engineering Research Center, University of California, Berkeley, CA, 1990.
- 12. Wu B, Ou J-P, Soong TT. Optimal placement of energy dissipation devices for three-dimensional structures. *Engineering Structures*, 1997; **19**(2): 113-125.
- 13. Goel RK. Effects of supplemental viscous damping on seismic response of asymmetric-plan systems. *Earthquake Engineering and Structural Dynamics*, 1998; **27**(2): 125-141.
- 14. Takewaki I, Yoshitomi S, Uetani K, Tsuji M. Non-monotonic optimal damper placement via steepest direction search. *Earthquake Engineering and Structural Dynamics*, 1999; **28**(6): 655-670.
- 15. Arfiadi Y, Muhammad NSH. Passive and active control of three-dimensional buildings. *Earthquake Engineering and Structural Dynamics*, 2000; **29**(3): 377-396.
- 16. Goel RK. Seismic behaviour of asymmetric buildings with supplemental damping. *Earthquake Engineering and Structural Dynamics*, 2000; **29**(3): 461-480.
- 17. Peakau OA, Dasgupta B, Bedair H. Improved deployment of friction dampers in asymmetric multistory buildings. *Proceedings of the 12th World Conference on Earthquake Engineering*. Auckland, New Zealand, 2000.
- 18. Goel RK, Booker CA. Effects of supplemental viscous damping on inelastic seismic response of asymmetric systems. *Earthquake Engineering and Structural Dynamics*, 2001; **30**(3): 411-430.
- 19. Lin WH, Chopra AK. Understanding and predicting effects of supplemental viscous damping on seismic response of asymmetric one-storey systems. *Earthquake Engineering and Structural Dynamics*, 2001; **30**(10): 1475-1494.
- Goel RK. Seismic response study of asymmetric systems with linear and nonlinear fluid viscous dampers. *Report No. CP/SEAM-2002/06*, Department of Civil & Environmental Engineering, California Polytechnic State University, San Luis Obispo, CA, 2002.
- 21. Lin WH, Chopra AK. Earthquake response of elastic SDF systems with non-linear fluid viscous dampers. *Earthquake Engineering and Structural Dynamics*, 2002; **31**(9): 1623-1642.
- 22. Samali B, Wu YM, Li J. Shake table tests on a mass eccentric model with base isolation. *Earthquake Engineering and Structural Dynamics*, 2003; **32**: 1353-1372.
- 23. Yoshida O, Dyke SJ, Giacosa LM, Truman KZ. Experimental verification of torsional response control of asymmetric buildings using MR dampers. *Earthquake Engineering and Structural Dynamics*, 2003; **32**: 2085-2105.
- 24. Lin WH, Chopra AK. Improving the seismic response of asymmetric one-story systems by supplemental viscous damping. *Proceedings of the Seventh U.S. National Conference on Earthquake Engineering*. Engineering Research Institute, Oakland, California, Boston, 2002.
- 25. Seleemah AA, Constantinou MC. Investigation of seismic response of buildings with linear and nonlinear fluid viscous dampers. *Report No. NCEER-97-0004*, National Center for Earthquake Engineering Research, Buffalo, New York, 1997.

- 26. Soong TT, Dargush GF. *Passive energy dissipation systems in structural engineering*. Wiley: New York, 1997.
- 27. Lin WH, Chopra AK. Asymmetric one-story elastic systems with nonlinear viscous and viscoelastic dampers: Earthquake response. *Earthquake Engineering and Structural Dynamics*, 2003; **32**(4): 555-577.
- Lin WH, Chopra AK. Asymmetric one-story elastic systems with nonlinear viscous and viscoelastic dampers: Simplified analysis and supplemental damping system design. *Earthquake Engineering and Structural Dynamics*, 2003; **32**(4): 579-596.
- 29. Pekcan G, Mander JB, Chen SC. Fundamental consideration for the design of non-linear viscous dampers. *Earthquake Engineering and Structural Dynamics*, 1999; **28**(11): 1405-1425.
- 30. Hanson RD, Soong TT. Seismic design with supplemental energy dissipation devices. Earthquake Engineering Research Institute: Oakland, CA, 2001.
- 31. Soong TT, Constantinou MC. *Passive and active structural vibration control in Civil Engineering*. Springer: New York, 1994.
- 32. Chopra AK. Dynamics of Structures: Theory and Applications to Earthquake Engineering (2nd edn.). Prentice Hall: Upper Saddle River, NJ, 2001.
- 33. Filiatrault A, Trebmblay R, Wanitkorkul A. Performance evaluation of passive damping systems for the seismic retrofit of steel moment-resisting frames subjected to near-field ground motions. *Earthquake Spectra*, 2001; **17**(1): 427-456.
- 34. Goel RK. Seismic Response of linear and nonlinear asymmetric systems with nonlinear fluid viscous dampers. *Earthquake Engineering and Structural Dynamics*, 2004; **To Appear**.
- Somerville P, Smith N, Punyamurthula S, Sun J. Development of ground motion time histories for phase 2 of the FEMA/SAC steel project. *Report No. SAC Background Document Report No. SAC/BD-9/04*, SAC Joint Venture, 555 University Ave., Sacramento, CA, 1997.
- 36. Benjamin JR, Cornell CA, *Probability, Statistics, and Decision for Civil Engineers*. 1970, McGraw-Hill: New York. p. 684.
- 37. Tso WK, Smith RSH. Re-evaluation of seismic torsional provisions. *Earthquake Engineering and Structural Dynamics*, 1999; **28**(8): 899-917.
- 38. Pauley T. Seismic torsional effects on ductile structural wall systems. *Journal of Earthquake Engineering*, 1997; **1**(4): 721-745.
- 39. Asher JW, Young RP, Ewing RD. Seismic isolation design of the San Bernardino county medical center replacement project. *Journal of Structure and Design of Tall Buildings*, 1996; **5**(4): 265-279.
- 40. Goel RK, Chopra AK. Inelastic seismic response of one-story, asymmetric-plan systems. *Report No. UCB/EERC-90/14*, Earthquake Engineering Research Center, University of California, Berkeley, Ca, 1990.
- 41. Hejal R, Chopra AK. Earthquake response of torsionally-coupled buildings. *Report No. UC/EERC-*87/20, Earthquake Engineering Research Center, University of California, Berkeley, CA, 1987.