

CHARACTERIZATION OF SOURCE MODELS OF SHALLOW INTRASLAB EARTHQUAKES USING STRONG MOTION DATA

Kimiyuki ASANO¹, Tomotaka IWATA², and Kojiro IRIKURA³

SUMMARY

Several differences of observed ground motion characteristics between crustal and intraslab earthquakes seem to be caused by not only propagation-path but also source characteristics. We studied the characterization of source models for shallow intraslab earthquakes based on strong motion simulations. Appropriate source models of several shallow intraslab earthquakes (M_W 5.2 - 7.0) that occurred in Japan were constructed to explain the broadband ground motion based on strong motion simulations using the empirical Green's function method. Our source model is expressed by one or several rectangular regions called strong motion generation area on an assumed fault plane, which can be thought to be equivalent to the asperities of heterogeneous source model by previous studies. We summarized the results and found that the strong motion generation area of the source model for each shallow intraslab earthquake is smaller than the prediction by the empirical relationship for inland crustal earthquakes proposed by Somerville et al. (1999). This means that the stress drop on the asperity or the strong motion generation area of a shallow intraslab earthquake is higher than that of an inland crustal earthquake. Among shallow intraslab earthquakes, relatively deeper event with the source depth of about 70 - 100 km has very high stress drop, that is more than 100 MPa, though shallower events with the source depth of about 30 km has relatively low stress drop, that is almost same or slightly higher than inland crustal events. Our result suggests that the stress drop on the asperity of shallow intraslab earthquakes depends on its depth. When we assume the value of the stress drop in case of the strong motion prediction for an intraslab earthquake, we have to consider include the focal-depth dependence of the stress drop.

INTRODUCTION

Shallow intraslab earthquakes occurring in subducting slab bring strong ground motion on surface despite its relatively deeper focal depths compared with inland crustal earthquakes. For engineering purpose, empirical attenuation relationships for peak ground acceleration and velocity have been developed considering the difference in the type of earthquake source and the focal depth by Si and Midorikawa [1]. According to their attenuation relationships, the peak ground motion from an intraslab event is larger than that from an interplate event. Such a large ground motion will be caused by not only the low-attenuation (high Q-value) along the propagation path but also the high stress drop on the source. Compared to

¹ Disaster Prevention Research Institute, Kyoto University, Gokasho, Uji, Kyoto 611-0011, Japan.

² Disaster Prevention Research Institute, Kyoto University, Gokasho, Uji, Kyoto 611-0011, Japan.

³ Disaster Prevention Research Institute, Kyoto University, Gokasho, Uji, Kyoto 611-0011, Japan.

shallow crustal earthquakes occurring at inland regions and interplate earthquakes occurring at subducting plate boundary regions, the study on source characteristics of shallow intraslab earthquakes in the view of strong motion seismology are not sufficient because the number of observed events seems to be smaller than other types of earthquakes and the place of large intraslab earthquake occurrences is believed to be limited. These intraslab earthquakes are thought to be related to the dehydration of hydrated oceanic crust and serpentinized mantle [2].

In recent years, Japan has been suffered by two large shallow intraslab earthquakes, which were the 2001 Geiyo earthquake and the 2003 off Miyagi earthquake. The strong motion waveforms from these earthquakes have been obtained through the dense Japanese strong motion networks, the K-NET [3] and the KiK-net [4], operated by the National Research Institute for Earth Science and Disaster Prevention (NIED). In this paper, we call the intraslab earthquake occurring at the depth of about 30-100 km the shallow intraslab earthquake. The detailed source processes of large earthquakes mentioned above have been obtained by several authors through the kinematic waveform inversion using the strong motion data [5-8]. However, the frequency range for these analyses is restricted to lower than about 1Hz because of the accuracy in the underground structure information to calculate Green's functions. To explain the realistic strong ground motions from shallow intraslab earthquakes quantitatively, it is needed to take more wide-range including high-frequency components of ground motions in consideration. One of the effective methods to simulate broadband ground motions is employment of observed aftershock records as the empirical Green's functions. Irikura [9] has developed the methodology to simulate strong ground motions using empirical Green's functions based on a scaling relationship of the ω^{-2} source spectrum [10]. The waveform for a large event is synthesized by summing the records of small events with corrections for the difference in the slip velocity time function between the large and small events following the scaling laws. Successive source modeling by the empirical Green's function method [9] has been done by Kamae and Irikura [11, 12], Ikeda et al. [13], Miyake et al. [14], Morikawa et al. [15], and others. In this study, we will construct source models for seven large and moderate-size shallow intraslab earthquakes by the forward waveform modeling using the empirical Green's function method [14], and will discuss on some remarkable features of obtained source models.

METHODOLOGY AND DATA

Methodology

In this study, a characterized source model consisting one or several "strong motion generation areas" in the fault plane is assumed. The strong motion generation area is defined as the extended area having relatively large slip velocity within the total rupture area [14]. We assume that the area has uniform slip and rise time. For broadband strong motion simulation up to about 10 Hz using the empirical Green's function method [9], such a simple source model is able to reproduce observed ground motions and is confirmed that the strong motion generation area is equivalent to the asperity area characterized from the heterogeneous slip distribution estimated by the kinematic waveform inversion using low-frequency waveforms [11-16].

We determined the number and the location of strong motion generation areas, the size and the rise time of each strong motion generation area, and the rupture propagation velocity by the forward modeling using the empirical Green's function method. Radial rupture propagation inside each strong motion generation area is also assumed. The best source model is chosen to minimize the residual of displacement waveforms and envelopes of acceleration waveforms using the criterion proposed by Miyake *et al.* [14]. The detailed description about the forward modeling and the summation technique of the empirical Green's function method are written by Irikura [9] and Miyake *et al.* [14].

Analyzed events and data set

We have analyzed seven shallow intraslab earthquakes listed in Table 1. The locations of epicenters are also indicated in Fig.1. The source mechanism determined from the moment tensor inversion using broadband seismograph data by the F-net and the Harvard University CMT project is also shown in Fig.1 using lower hemisphere projection. The focal depths of these events range from 30 to 72 km. Magnitudes determined by the Japan Meteorological Agency (JMA) are from 5.3 to 7.1. Horizontal components of the S-wave part at four strong motion stations are used to construct the source model by the forward waveform modeling.

Table 1: Information of target events and small events used as empirical Green's functions										
Event No	o. Origin time (JST)	Lat. (deg)	Long. (deg)	Depth (km)	$M_{\rm JMA}$	M_0 (Nm) / M_W				
1m	1997/03/16 14:51	34.925°N	137.528°E	39.12	5.9	2.97×10 ¹⁷ /5.6				
1s	1997/03/16 14:53	34.901°N	137.515°E	36.21	4.0	N.A.				
2m	1999/08/21 05:33	34.028°N	135.473°E	65.83	5.6	2.79×10 ¹⁷ / 5.6				
2s	2000/06/02 15:05	34.002°N	135.407°E	59.85	4.1	2.10×10 ¹⁵ /4.2				
3m	2000/01/28 23:21	43.006°N	146.749°E	58.51	7.0	1.21×10 ¹⁹ /6.7				
3s	2000/09/03 20:01	42.984°N	146.846°E	49.40	5.7	1.39×10 ¹⁷ / 5.4				
4m	2001/03/24 15:27	34.129°N	132.696°E	46.46	6.7	1.51×10 ¹⁹ /6.8				
4s	2001/03/26 05:40	34.114°N	132.712°E	45.86	5.2	4.76×10 ¹⁶ / 5.1				
5m	2001/04/03 23:57	35.021°N	138.097°E	30.34	5.3	8.17×10 ¹⁶ /5.2				
5s	2001/04/04 00:04	35.011°N	138.089°E	31.31	4.1	8.73×10 ¹⁴ /3.9				
6m	2001/04/25 23:40	32.796°N	132.342°E	39.30	5.8	4.00×10 ¹⁷ /5.7				
6s	1999/01/25 05:03	32.694°N	132.286°E	39.23	3.9	1.33×10 ¹⁵ /4.0				
7m	2003/05/26 18:24	38.818°N	141.654°E	72.03	7.1	3.49×10 ¹⁹ /7.0				
7s	2003/05/27 00:44	38.948°N	141.665°E	68.52	4.9	1.43×10 ¹⁶ /4.7				

Event No. with 'm' indicates the mainshock that is studied as the target event, and that with 's' indicates the small event that is used as the empirical Green's function.

Hypocentral information is provided from the Japan Meteorological Agency (JMA).

Seismic moment (M_0) was determined by the F-net (Full Range Seismograph Network of Japan), NIED [17]. These data is available via the World Wide Web (http://www.fnet.bosai.go.jp/).



Figure 1: Locations and mechanisms of events studied

RESULTS

The 2001 Geiyo earthquake

The 2001 Geiyo earthquake (M_{JMA} =6.7, M_W =6.8) occurred at the depth of 46 km within the Philippine Sea slab on March 24, 2002 (JST). At this region, a large historical intraslab earthquake called the 1905 Geiyo earthquake (M=7.2) has occurred. The epicenters of the target and the small events are shown by the large and the small stars in Fig.2. Strong motion stations used for the source modeling are indicated by solid triangles in Fig.2.



Our forward modeling result suggests that the 2001 Geiyo earthquake has two strong motion generation areas. The obtained source model is shown in Fig.3. The large star in Fig.3 is the starting point of the whole rupture fixed at the hypocenter determined by the JMA, and the small star is the rupture starting point for the strong motion generation area. The rupture of the second (southern) strong motion generation area.



Figure 3: Obtained source model of the 2001 Geiyo earthquake

Observed and synthetic acceleration, velocity, and displacement waveforms of each component are shown in Fig. 4. These records are band-pass filtered between 0.2 and 10 Hz. The number between observed and synthetic waveforms of each component is the maximum amplitude of the observed records. Observed waveforms are well reproduced by synthetic waveforms.



Figure 4: Comparison of observed and synthetic waveforms for the 2001 Geiyo earthquake

The 2003 Off-Miyagi earthquake

The 2003 Off-Miyagi earthquake (M_{JMA} =7.1, M_W =7.0) occurred at the depth of 72 km near the coast of Northeastern Honshu, Japan, within the Pacific slab on May 26, 2002 (JST). The epicenters of the target and the small events are shown by the large and the small stars in Fig.5. Strong motion stations used for the source modeling are indicated by solid triangles in Fig.5.



Our forward modeling result suggests that the 2003 Off-Miyagi earthquake has three strong motion generation areas within a total rupture area. The obtained source model is shown in Fig. 6. This spatial

distribution of strong motion generation area is close to the large slip area from the kinematic waveform inversion [7]. The large star in Fig.3 is the starting point of the whole rupture fixed at the hypocenter determined by the JMA, and the small star is the rupture starting point for the strong motion generation area. The ruptures of the strong motion generation area B and C started at 0.36 s and 3.28 s after the rupture of the strong motion generation area A, respectively.



Figure 6: Obtained source model of the 2003 Off-Miyagi earthquake

Observed and synthetic acceleration, velocity, and displacement waveforms of each component are shown in Fig. 7. These records are band-pass filtered between 0.3 and 10 Hz. The number between observed and synthetic waveforms of each component is the maximum amplitude of the observed records. Observed waveforms are well reproduced by synthetic waveforms.



Figure 7: Comparison of observed and synthetic waveforms for the 2003 Off-Miyagi earthquake

Summary of all events

Source parameters of all events analyzed here are listed in Table 2.

Table 2. Obtailed parameters of outoing motion deneration Areas obtailed in this study									
No.	Length (km)	Width (km)	Area (km ²)	Rise time (sec)	V₁ (km/s)	Δσ (MPa)			
1m	1.5	1.8	2.7	0.09	3.05	N.A.			
2m	1.2	1.2	1.44	0.04	4.2	314			
3m	4.4	5.6	24.64	0.12	3.7	261			
4m	7.2 and 5.4	4.6 and 4.6	57.96	0.28 and 0.21	2.7	47 and 41			
5m	1.8	2.2	3.96	0.04	3.1	23			
6m	2.2	3.4	7.48	0.12	3.4	19			
7m	3.0, 4.0,	3.0, 4.0,	61.0	0.18, 0.24,	2.75	105, 105,			
	and 6.0	and 6.0		and 0.36		and 105			

Event 4m and 7m has two and three strong motion generation areas, respectively.

 $V_{\rm r}$ is the rupture propagation velocity inside the strong motion generation area.

 $\Delta\sigma$ is the stress drop on the strong motion generation area calculated assuming a circular crack [18, 19].

DISCUSSION

Scaling relationship between strong motion generation area and seismic moment

Strong motion generation area obtained here is plotted against the seismic moment in Fig.8. Strong motion generation areas for two great intraslab earthquakes in Hokkaido derived by Morikawa *et al.* [15] are also plotted in the same figure. For comparison, strong motion generation areas of inland crustal earthquakes estimated by the forward waveform modeling using the empirical Green's function method [11-14] are plotted by squares in Fig.8. The solid line in Fig.8 is the empirical relationship between combined area of asperities and seismic moment proposed by Somerville *et al.* [20]. Miyake *et al.* [14] has concluded that strong motion generation area of inland crustal earthquakes follow the empirical relationship by Somerville *et al.* [20]. However, shallow intraslab earthquakes studied in this study show smaller strong motion generation area than that predicted from the empirical relationship by Somerville *et al.* [20]. Since their empirical relationship is a self-similar relationship with constant stress drop on asperities, it means the stress drop on strong motion generation area or asperities of shallow intraslab earthquakes are larger than that of inland crustal earthquake. That is a quite important characteristic for the source modeling of shallow intraslab earthquakes.



Figure 8: Relationship between strong motion generation area and seismic moment

Depth dependence of stress drop on strong motion generation area

Fig.9 shows the relationship between the stress drop on strong motion generation area and the depth of the center of strong motion generation area. Solid circles indicate normal-fault intraslab events in the Philippine Sea slab, respectively. Open squares indicate reverse-fault events in Pacific slab. Horizontal bars accompanying with these symbols correspond to the spatial extent of strong motion generation area in the depth direction. The relation shows the depth dependence of stress drops, in which the deeper event has larger stress drop. In addition, the reverse fault intraslab events seem to have relatively larger stress drop than the normal fault events. Another possible controlling factor for the difference in stress drop is the regional difference between the Pacific slab and Philippine Sea slab.



Figure 9: Relationship between the stress drop on strong motion generation area and the depth

CONCLUSIONS

Source modeling of seven shallow intraslab earthquakes occurred in Japan were studied via the forward modeling using the empirical Green's function method. Obtained result indicate that strong motion generation area of shallow intraslab earthquakes are smaller then the predicted values from the empirical relationship between seismic moment and combined area of asperities for inland crustal earthquakes. And, the stress drop on the strong motion generation area seems to depend on its depth, which should be one of important source characteristics for shallow intraslab earthquakes. These results suggests that we need to consider the depth dependence of the stress drop on the strong motion generation area or the asperity in case of the source modeling for the strong motion prediction for shallow intraslab earthquakes.

ACKNOWLEDGMENTS

We would like to thank the National Research Institute for Earth Science and Disaster Prevention (NIED) for strong motion data used in this study, the Japan Meteorological Agency (JMA) for providing hypocentral information, and the F-net/NIED and the Harvard University CMT Project for moment tensor solutions catalog. This study is partially supported by the study on characterization of earthquake faults and crustal structure of special project for earthquake disaster mitigation in urban areas by the Ministry of Education, Culture, Sports, Science, and Technology (MEXT), Japan. We used the Generic Mapping Tools (Wessel and Smith, 1998) to draw some of figures in this paper.

REFERENCES

- 1. Si H, and Midorikawa S. "New attenuation relationships for peak ground acceleration and velocity considering effects of fault type and site condition." Journal of Structural and Construction Engineering, Architectural Institute of Japan 1999; 523: 63-70. (in Japanese with English abstract)
- Seno T, and Yamazaki T. "Low-frequency tremors, intraslab and interplate earthquakes in Southwest Japan - from a viewpoint of slab dehydration." Geophysical Research Letters 2003; 30(22): 2171, doi: 10.1029/2003GL018349.
- 3. Kinoshita S. "Kyoshin Net (K-NET)." Seismological Research Letters 1998; 69(4): 309-322.
- 4. Aoi S, Obara K, Hori S, Kasahara K, and Okada Y. "New strong-motion observation network: KiK-net." Eos, Transactions, American Geophysical Union 2000; 81(48): F329.
- 5. Sekiguchi H, and Iwata T. "Rupture process and strong ground motion of the 2001 Geiyo earthquake." Chikyu Monthly 2002, Special edition 38: 239-246. (in Japanese)
- 6. Kakehi Y. "Source and path modeling of the 2001 Geiyo earthquake and the strong ground motions." Eos, Transactions, American Geophysical Union 2003; 84(46): F1128.
- Aoi S, Sekiguchi H, Honda R, Morikawa N, Kunugi T, and Fujiwara H. "Ground motion and rupture process of the 26 May 2003 Off-Miyagi earthquake obtained from strong motion data of K-NET and KiK-net." Programme and Abstracts, the Seismological Society of Japan, 2003, Fall Meeting, Kyoto, Japan. Paper no. A077, Tokyo: Seismological Society of Japan, 2003. (in Japanese)
- 8. Okada T, and Hasegawa A. "The M7.0 May 26, 2003 Off-shore Miyagi Prefecture earthquake in Northeast Japan: Source process and aftershock distribution of an intra-slab event." Earth, Planets and Space 2004, in press.
- 9. Irikura K. "Prediction of strong acceleration motions using empirical Green's function." Proceedings of the 7th Japan Earthquake Engineering Symposium, Tokyo, Japan. Tokyo: Earthquake Engineering Research Liaison Committee, Science Council of Japan, 1986: 151-156.
- 10. Aki K. "Scaling law of seismic spectrum." Journal of Geophysical Research 1967; 72(4): 1217-1231.
- Kamae K, and Irikura K. "Source model of the 1995 Hyogo-ken Nanbu earthquake and simulation of near-source ground motion." Bulletin of the Seismological Society of America 1998; 88(2): 400-412.
- 12. Kamae K, and Irikura K. "A source model of the 1994 Northridge earthquake (Mw=6.7)." Proceedings of the 10th Japan Earthquake Engineering Symposium, Yokohama, Japan. Tokyo: Architectural Institute of Japan, 1998: 643-648. (in Japanese with English abstract)
- Ikeda T, Kamae K, Miwa S, and Irikura K. "Source characterization and strong ground motion simulation of the 2000 Tottori-ken Seibu earthquake using the empirical Green's function method." Journal of Structural and Construction Engineering, Architectural Institute of Japan 2002; 561: 37-45. (in Japanese with English abstract)
- 14. Miyake H, Iwata T, and Irikura K. "Source characterization for broadband ground-motion simulation: kinematic heterogeneous source model and strong motion generation area." Bulletin of the Seismological Society of America 2003; 93(6): 2531-2545.
- 15. Morikawa N, Sasatani T., and Fujiwara H. "Construction of source models of intra-slab earthquakes using empirical Green's function method." Proceedings of the 11th Japan Earthquake Engineering Symposium, Tokyo, Japan. Tokyo: Japanese Geotechnical Society, 2002: 133-138.
- 16. Miyakoshi K, Kagawa T, Sekiguchi H, Iwata T, and Irikura K. "Source characterization of inland earthquakes in Japan using source inversion results." Proceedings of the 12th World Conference on Earthquake Engineering, Auckland, New Zealand. Paper no. 1850. Upper Hutt, New Zealand: New Zealand Society for Earthquake Engineering, 2000.
- 17. Fukuyama E, Ishida M, Dreger DS, and Kawai H. "Automated seismic moment tensor determination using on-line broadband seismic waveforms." Zisin, Second series (Journal of the Seismological Society of Japan) 1998; 51(1): 149-156. (in Japanese with English abstract)

- 18. Brune JN. "Tectonic stress and the spectra of seismic shear waves from earthquakes." Journal of Geophysical Research 1970; 75(26): 4997-5009.
- 19. Brune JN. "Tectonic stress and the spectra of seismic shear waves from earthquakes; Correction." Journal of Geophysical Research 1971; 76(20): 5002.
- 20. Somerville P, Irikura K, Graves R, Sawada S, Wald D, Abrahamson N, Iwasaki Y, Kagawa T, Smith N, and Kowada A. "Characterizing crustal earthquake slip models for the prediction of strong ground motion." Seismological Research Letters 1999; 70(1): 59-80.